

Technical Data Sheet

General and Commercial Data


<i>Product Tye</i>	Indoor – Emergency Lighting
<i>Series</i>	Stile +
<i>Models</i>	19502
<i>Description</i>	STILE+ LED 11W SE/SA RM 1/3H
<i>Available colors</i>	White RAL 9003
<i>Application</i>	Emergency Lighting Residential, Tertiary, Offices
<i>Net Weight [kg]</i>	0,25
<i>Dimensions [mm]</i>	280x119x46
<i>Pieces x Pack Sing / Mult</i>	1 / 12



Dimensioni mm			Distanza visibilità (DV)
L	B	H	
280	119	46	21 m

Technical Characteristics

<i>Insulation Class</i>	II
<i>IP Code</i>	42
<i>Impact Resistance IK Rating</i>	5
<i>Fire Resistance_ Glow Wire[°C]</i>	850
<i>Materials</i>	Polycarbonate
<i>Emergency Supply Source</i>	Self Contained
<i>Emergency Operation Mode</i>	Maintained / Non Maintained
<i>Battery</i>	LiFe 3.2V 0.5Ah
<i>Charge time [h]</i>	24
<i>Duration [h]</i>	1/3
<i>Diagnostic System</i>	No diagnostic
<i>Emergency Control Mode</i>	Automatic with Rest Mode
<i>Visibility Distance (EN1838) [m]</i>	21
<i>Range of ambient temperature [°C]</i>	0 ÷ 40
<i>Rated Supply [V]</i>	230
<i>Frequency [Hz]</i>	50
<i>Luminary Absorption [W]</i>	0.8
<i>Flux in Emergency mode [lm]</i>	120/50
<i>Light Source</i>	LED - CCT 4000 K - CRI 80
<i>Led Expected life [h]</i>	50000



Photometric Parameters

<i>Measurement</i>	19502e
<i>CIE code</i>	[39,73,95,100,100]
<i>Optic</i>	Symmetric _ Diffusive

Standard

CEI EN 62471
CEI EN 60598-2-2
CEI EN 60598-2-22
2014/30/EU
2014/35/EU

Notes

Acc.: Safety Sign screen (see catalogue for details)
Acc.: Bracket and particular for installation (see catalogue for details)