

PANORAMA PUBLIC LIGHTING

ECONOMIC AND EFFICIENT LIGHTING



ENERGY
EFFICIENCY
CLASS

A+



CATALOGUE NUMBER	EAN	POWER CONSUMPTION	LUMINOUS FLUX	COLOR TEMPERATURE	PROTECTION CLASS	LIFESPAN	DIMENSIONS	WEIGHT	SUPPORT ARM DIAMETER
SL403040-6HE	8596238001046	30W	3 600lm	4000K	IP65	50 000h	400x170x60mm	1,6kg	53mm
SL506040-6HE	8596238001053	60W	7 200lm	4000K	IP65	50 000h	500x215x80mm	2,1kg	53mm
SL628040-6HE	8596238001084	80W	9 600lm	4000K	IP65	50 000h	620x260x85mm	3,2kg	64mm
SL721040-6HE	8596238001114	100W	12 000lm	4000K	IP65	50 000h	720x280x95mm	4,25kg	64mm
SL533040-6HE	8596238001060	30W	3 600lm	4000K	IP65	50 000h	530x250x100mm	2,6kg	61mm
SL536040-6HE	8596238001077	60W	7 200lm	4000K	IP65	50 000h	530x250x100mm	2,9kg	61mm
SL658040-6HE	8596238001107	80W	9 600lm	4000K	IP65	50 000h	650x250x120mm	3,6kg	61mm
SL651040-6HE	8596238001091	100W	12 000lm	4000K	IP65	50 000h	650x250x120mm	3,7kg	61mm

C O R P

VOLTAGE 230V

FREQUENCY 50Hz

OPERATING TEMPERATURE -25°- +40°C

CRI/Ra ≥70

IP RATING IP65