

GU10 LED SPOT LIGHTING

RECESSED AND SPOT LIGHTING



ONLINE INFO

SAVINGS
UP TO



90%

ENERGY
EFFICIENCY
CLASS

A+



A



B

	CATALOGUE NUMBER	EAN	SOCKET	POWER CONSUMPTION	LUMINOUS FLUX	REPLACEMENT FOR	BEAM ANGLE	COLOR TEMPERATURE	DIMMABLE	LIFESPAN	Ø DIAMETER	HEIGHT
A	GU103530-5	9009789005863	GU10	3,5W	240lm	-	100°	3000K	NO	25000h	50mm	55mm
A	GU103540-5	9009789005870	GU10	3W	230lm	-	100°	4000K	NO	25000h	50mm	55mm
A	GU100530-5	8596238000087	GU10	5W	410lm	-	100°	3000K	NO	25000h	50mm	55mm
A	GU100540-5	9009789006303	GU10	5W	410lm	-	100°	4000K	NO	25000h	50mm	55mm
A	GU100530-5D	9009789005887	GU10	5W	400lm	-	100°	3000K	YES	25000h	50mm	55mm
B	GU100730-2	9009789003876	GU10	7W	450lm	-	36°	3000K	NO	25000h	52mm	65mm
A	GU100730-4	9009789006679	GU10	7W	560lm	-	100°	3000K	NO	25000h	50mm	55mm
A	GU100740-2	8596238000483	GU10	7W	560lm	-	100°	4000K	NO	25000h	50mm	55mm
A	GU100730-6D	8596238000759	GU10	7W	560lm	-	100°	3000K	YES	25000h	50mm	56mm

C O R P

VOLTAGE 230V

OPERATING TEMPERATURE -20°- +40°C

CRI/Ra ≥80

IP RATING IP20