

MR16/GU5.3 LED SPOT LIGHTING

RECESSED AND SPOT LIGHTING



ONLINE INFO
SAVINGS
UP TO



80%

ENERGY
EFFICIENCY
CLASS
A+



A

	CATALOGUE NUMBER	EAN	SOCKET	POWER CONSUMPTION	LUMINOUS FLUX	VOLTAGE	BEAM ANGLE	COLOR TEMPERATURE	DIMMABLE	LIFESPAN	Ø DIAMETER	HEIGHT
A	MR160430-5	9009789005467	GU5,3	4W	320lm	12V	38°	3000K	NO	25000h	50mm	53mm
A	MR163530-4	9009789006259	GU5,3	3,5W	230lm	12V	100°	3000K	NO	25000h	50mm	53mm
A	MR163540-5	9009789005856	GU5,3	3,5W	240lm	12V	100°	4000K	NO	25000h	50mm	53mm
A	MR160630-5	8596238000094	GU5,3	6W	470lm	12V	100°	3000K	NO	25000h	50mm	53mm
A	MR160640-5	8596238000100	GU5,3	6W	470lm	12V	100°	4000K	NO	25000h	50mm	53mm

C O R P

VOLTAGE 12V

OPERATING TEMPERATURE -20°- +40°C

CRI/Ra ≥80

IP RATING IP20