

T8 SMD LED TUBES

STANDARD AND HIGH EFFICIENCY TUBES WITH THE LATEST TECHNOLOGY



ONLINE INFO


SAVINGS
UP TO



50%

ENERGY
EFFICIENCY
CLASS

A+



	CATALOGUE NUMBER	EAN	SOC- KET	POWER CONSUMPTION	LUMINOUS FLUX	BEAM ANGLE	COLOR TEMPERATURE	WEIGHT	EFFICIENCY	LIFESPAN	DIMENSIONS
A	T8060940-3FM	9009789005061	G13	9W	1020lm	120°	4000K	145g	120lm/W	50 000h	600x28mm
B	T8121840-3FM	9009789005078	G13	18W	2160lm	120°	4000K	285g	120lm/W	50 000h	1200x28mm
B	T8121850-3FM	9009789005085	G13	18W	2160lm	120°	5000K	285g	120lm/W	50 000h	1200x28mm
C	T8152340-3FM	9009789005092	G13	23W	2760lm	120°	4000K	315g	120lm/W	50 000h	1500x28mm
D	T8152350-3FM	9009789005306	G13	23W	2760lm	120°	5000K	315g	120lm/W	50 000h	1500x28mm
high performance tubes											
E	T8121840-3SE	9009789006464	G13	18W	2600lm	120°	4000K	285g	144lm/W	50 000h	1200x28mm
F	T8121850-3SE	9009789006471	G13	18W	2600lm	120°	5000K	285g	144lm/W	50 000h	1200x28mm
G	T8152840-3SE	9009789006501	G13	28W	4004lm	120°	4000K	315g	143lm/W	50 000h	1500x28mm
H	T8152850-3SE	9009789006518	G13	28W	4004lm	120°	5000K	315g	143lm/W	50 000h	1500x28mm

C O R P

VOLTAGE **230V**

OPERATING TEMPERATURE **-20° - +40°C**

CRI/Ra **≥80**

IP RATING **IP20**