



T8 SMD LED TUBES

LED T8 tube brings savings of electricity up to 50%.

- *Lightweight durable design*
- *High quality LED chips*
- *Optimal heat dissipation*
- *Lifespan 35 000h (L70)*
- *LED starter included*
- *Professional and domestic application*

Advanced SMD LED chips proven LM-80 test achieve stable performance and reach lifetime of 35 000hrs. Milk enclosure ensures glare-free light scattering.

T8 SMD LED TUBES

STANDARD AND HIGH EFFICIENCY TUBES
WITH THE LATEST TECHNOLOGY



ONLINE INFO




SAVINGS
UP TO

50%

ENERGY
EFFICIENCY
CLASS

A+



CATALOGUE NUMBER	EAN	SOCKET	POWER CONSUMPTION	LUMINOUS FLUX	BEAM ANGLE	COLOR TEMPERATURE	DIMMABLE	LIFESPAN	DIMENSIONS
T8060940-3FM	9009789005061	G13	9W	1020lm	120°	4000K	NO	35 000h	600x28mm
T8121840-3FM	9009789005078	G13	18W	2160lm	120°	4000K	NO	35 000h	1200x28mm
T8121850-3FM	9009789005085	G13	18W	2160lm	120°	5000K	NO	35 000h	1200x28mm
T8152440-3FM	9009789005092	G13	24W	2760lm	120°	4000K	NO	35 000h	1500x28mm
T8152450-3FM	9009789005306	G13	24W	2760lm	120°	5000K	NO	35 000h	1500x28mm
HIGH EFFICIENCY TUBES									
T8121840-3SE	9009789006464	G13	18W	2574lm	120°	4000K	NO	35 000h	1200x28mm
T8121850-3SE	9009789006471	G13	18W	2574lm	120°	5000K	NO	35 000h	1200x28mm
T8152340-3SE	9009789006488	G13	23W	3289lm	120°	4000K	NO	35 000h	1500x28mm
T8152350-3SE	9009789006495	G13	23W	3289lm	120°	5000K	NO	35 000h	1500x28mm
T8152840-3SE	9009789006501	G13	28W	4004lm	120°	4000K	NO	35 000h	1500x28mm
T8152850-3SE	9009789006518	G13	28W	4004lm	120°	5000K	NO	35 000h	1500x28mm



VOLTAGE **230V**

OPERATING TEMPERATURE **-20°- +40°C**

CRI/Ra **≥80**

IP RATING **IP20**