

LED CEILING PANELS

MODERN INTERIORS



ENERGY
EFFICIENCY
CLASS

A



CATALOGUE NUMBER	EAN	POWER CONSUMPTION	LUMINOUS FLUX	COLOR TEMPERATURE	BEAM ANGLE	LIFESPAN	DIMMABLE	DIMENSIONS	WEIGHT
LP616040-4E	9009789005733	60W	4500lm	4000K	120°	35 000h	NO	1200x600mm	7,55kg
LP314030-9	8596238000674	40W	3600lm	3000K	120°	35 000h	NO	1200x300mm	3,15kg
LP314040-9	8596238000599	40W	4000lm	4000K	120°	35 000h	NO	1200x300mm	3,15kg
LP664030-9	8596238000643	40W	3600lm	3000K	120°	35 000h	NO	600x600mm	2,5kg
LP664040-9	8596238000667	40W	4000lm	4000K	120°	35 000h	NO	600x600mm	2,5kg
LP632040-9	8596238000636	20W	2000lm	4000K	120°	35 000h	NO	600x300mm	2,8kg
LP332040-9	8596238000612	20W	2000lm	4000K	120°	35 000h	NO	300x300mm	1,1kg
LP332030-9	8596238000605	20W	1800lm	3000K	120°	35 000h	NO	300x300mm	1,1kg

C O R P

VOLTAGE 230V

OPERATING TEMPERATURE -20° - +40°C

CRI/Ra ≥80

IP RATING IP20