

LED FLOOD LIGHTS

COMPACT AND ENERGY-EFFICIENT



ENERGY
EFFICIENCY
CLASS

A



	CATALOGUE NUMBER	EAN	POWER CONSUMPTION	LUMINOUS FLUX	BEAM ANGLE	COLOR TEMPERATURE	LIFESPAN	FUNCTION	PROTECTION CLASS	WEIGHT	DIMENSIONS
A	FL132065-6	8596238001848	20W	1800lm	110°	6500K	25 000h	-	IP65	0,295kg	131x117x26mm
B	FL183065-6	8596238001916	30W	2 700lm	110°	6500K	25 000h	-	IP65	0,537kg	184x165x28mm
C	FL235065-6	8596238001862	50W	4 500lm	110°	6500K	25 000h	-	IP65	0,912kg	230x195x32mm
D	FL330165-6	8596238001879	100W	9 000lm	110°	6500K	25 000h	-	IP65	2,025kg	327x265x42mm
E	FL381565-6	8596238001886	150W	13 500lm	110°	6500K	25 000h	-	IP65	2,905kg	381x302x45mm
F	FL420265-6	8596238001893	200W	18 000lm	110°	6500K	25 000h	-	IP65	3,400kg	420x320x45mm
G	FL132065-PIR	8596238001954	20W	1800lm	110°	6500K	25 000h	PIR sensor	IP44	0,410kg	131x191x26mm
H	FL183065-PIR	8596238001961	30W	2 700lm	110°	6500K	25 000h	PIR sensor	IP44	0,625kg	184x232x28mm
I	FL235065-PIR	8596238001978	50W	4 500lm	110°	6500K	25 000h	PIR sensor	IP44	1,030kg	230x274x32mm
J	FL132065-STAND	8596238001985	20W	1800lm	110°	6500K	25 000h	stand	IP65	1,015kg	175x160x245mm
K	FL183065-STAND	8596238001992	30W	2 700lm	110°	6500K	25 000h	stand	IP65	1,319kg	215x215x325mm
L	FL235065-STAND	8596238002005	50W	4 500lm	110°	6500K	25 000h	stand	IP65	1,916kg	305x210x360mm
M	FL183065-TRIPOD1	8596238002012	30W	2 700lm	110°	6500K	25 000h	tripod	IP65	2,741kg	840x171x245mm
N	FL235065-TRIPOD1	8596238002029	50W	4 500lm	110°	6500K	25 000h	tripod	IP65	3,555kg	840x171x245mm
O	FL183065-TRIPOD2	8596238002036	2x30W	2x2 700lm	110°	6500K	25 000h	tripod	IP65	3,103kg	840x179x245mm
P	FL235065-TRIPOD2	8596238002043	2x50W	2x4 500lm	110°	6500K	25 000h	tripod	IP65	4,279kg	840x179x245mm

C O R P

VOLTAGE **230V**

OPERATING TEMPERATURE **-20°- +50°C**

CRI/Ra **≥75**

IP RATING **IP66**