



## LED LIGHT FIXTURES

**Recessed downlighters for  
universal applications in indoor  
commercial and home spaces.**

- IP44 rating
- Power consumption from 15W to 40W
- Simple installation
- Long lifespan
- Color temperature and dimming upon request
- Application: homes, hotels, museums,  
art galleries, offices

A wide range of beam angles and dimming on demand.

# LED LIGHT FIXTURES

## RECESSED LED LUMINAIRES



CATALOGUE NUMBER	POWER CONSUMPTION	LUMINOUS FLUX	BEAM ANGLE	COLOR TEMPERATURE	LIFESPAN	DIMENSIONS	MOUNTING DIMENSIONS
DL154027-1XX	<b>40W</b>	3800lm	15° / 24° / 36° / 60°	2700K	40 000h	Ø150x152mm	Ø140mm
DL153027-1XX	<b>30W</b>	3000lm	15° / 24° / 36° / 60°	2700K	40 000h	Ø150x152mm	Ø140mm
DL152527-1XX	<b>25W</b>	2400lm	15° / 24° / 36° / 60°	2700K	40 000h	Ø150x152mm	Ø140mm
DL112527-1XX	<b>25W</b>	2400lm	15° / 24° / 36° / 60°	2700K	40 000h	Ø110x130mm	Ø100mm
DL152027-1XX	<b>20W</b>	2000lm	15° / 24° / 36° / 60°	2700K	40 000h	Ø150x152mm	Ø140mm
DL112027-1XX	<b>20W</b>	2000lm	15° / 24° / 36° / 60°	2700K	40 000h	Ø110x130mm	Ø100mm
DL111527-1XX	<b>15W</b>	1500lm	15° / 24° / 36° / 60°	2700K	40 000h	Ø110x130mm	Ø100mm



VOLTAGE **230V**

OPERATING TEMPERATURE **-20°- +40°C**

CRI/Ra **≥80**

IP RATING **IP44**