

HIGH BAY

PROFESSIONAL LUMINAIRES
FOR DEMANDING CONDITIONS



ONLINE INFO



TESLA
LIGHTING

ENERGY
EFFICIENCY
CLASS

A



	CATALOGUE NUMBER	EAN	POWER CONSUMPTION	LUMINOUS FLUX	COLOR TEMPERATURE	BEAM ANGLE	LIFESPAN	DIMMABLE	DIMENSIONS	WEIGHT
A	IL261050-6CHED	8596238002067	100W	16 000lm	5000K	60°/70°/90°/110°	50 000h	YES 1-10V	Ø260x140mm	2,18kg
A	IL261550-6CHED	8596238002074	150W	24 000lm	5000K	60°/70°/90°/110°	50 000h	YES 1-10V	Ø260x140mm	2,18kg
A	IL282050-6CHED	8596238002081	200W	32 000lm	5000K	60°/70°/90°/110°	50 000h	YES 1-10V	Ø280x150mm	3,2kg
B	IL251050-4CHED	8596238001183	100W	14 000lm	5000K	60°/70°/90°/110°	50 000h	YES 1-10V	Ø252x180mm	3,9kg
B	IL251550-4CHED	8596238001169	150W	21 000lm	5000K	60°/70°/90°/110°	50 000h	YES 1-10V	Ø252x200mm	4,2kg
B	IL282050-4CHED	8596238001176	200W	27 000lm	5000K	60°/70°/90°/110°	50 000h	YES 1-10V	Ø280x228mm	6,8kg
B	IL282450-4CHED	8596238001190	240W	32 000lm	5000K	60°/70°/90°/110°	50 000h	YES 1-10V	Ø280x228mm	6,8kg

C O R P

VOLTAGE 90-305V AC

OPERATING TEMPERATURE -30°- +45°C

CRI/Ra ≥80

IP RATING IP65